



Frontend Components – CAMERA TS-1238 SC

Model	TS-1238 SC Reverse Camera
Image Sensor	NVP2431H + 1/3" CMOS AR0130
TV System	PAL/NTSC
Lens optional	2.1mm
Effective Pixel Arrey	1280H x 960 V
Min illumination	0.01Lux @(F1.2,AGC ON)
S/N Ratio	More than 60 dB, (AGC Off)
WDR	D-WDR
IR &Infrared LED Range	4 PCS IR LED) ,20m
Audio fuction	N/A
Horizontal angle of view	F2.1mm (H120°)
Work current	210mA
Tilt Adjusting	0-60 degree
Power Supply	12V DC ±10%
Dimensions	108×78×62mm
Net Weight	350 g
Weatherproof/WaterProof	IP67
Operational Temperature	-20 ~ +60 ° C
Operational humidity	20%~80%
vedio interface	Aircraft Round Connector Plug

Features:

- 1.NVP2431H + 1/3" CMOS AR0130 image sensor,
2. Support Rear installation (2.1mm);
3. IP67 Waterproof ;
4. Support IR function, infrared LED range 20m;
5. Easy installation to ceiling or wall;
6. Support D-WDR, Video effects can be optimized;
- 7.Support 12V DC ±10%,Low power consumption.



- 1---12VDC (+)
- 2---12VDC/GND (-)
- 3---N/A
- 4---Video

Dimensions:

